


Sigen Hybrid Inverter

5.0 – 30.0 kW Three Phase



- Battery ready, future proof
- DC/AC ratio up to 1.6
- Up to 4 MPP. trackers
- IP66 protection rating

Sigen Hybrid Inverter 5.0–30.0 kW Three Phase ¹

Sigen Hybrid	5.0 TP	6.0 TP	8.0 TP	10.0 TP	12.0 TP	15.0 TP	17.0 TP	20.0 TP	25.0 TP	30.0 TP	Units	
DC Input												
Max. PV power	8000	9600	12800	16000	19200	24000	27200	32000	40000	48000	W	
Max. DC input voltage						1100						V
Nominal DC input voltage						600						V
Start-up voltage						180						V
MPPT voltage range						160 ~ 1000						V
Number of MPP trackers	2			3			4					
Number of PV strings per MPPT						1						
Max. input current per MPPT						16						A
Max. short-circuit current per MPPT						20						A
AC Output (on-grid)												
Nominal output power	5000	6000	8000	10000	12000	15000	17000	20000	25000	30000	W	
Max. output apparent power	5500	6600	8800	11000	13200	16500	18700	22000	27500	33000	VA	
Nominal output current	7.6	9.1	12.2	15.2	18.2	22.8	25.8	30.4	38.0	45.5	A	
Max. output current	8.4	10.0	13.4	16.7	20.1	25.1	28.4	33.4	41.8	50.0	A	
Nominal output voltage						380 / 400						V
Nominal grid frequency						50 / 60						Hz
Power factor						0.8 leading ~ 0.8 lagging						
Total current harmonic distortion						THDi < 2%						
Efficiency												
Max. efficiency	98.1%	98.2%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.3%	98.4%		
European efficiency	96.1%	96.6%	97.1%	97.5%	97.7%	97.9%	97.9%	97.9%	98.0%	98.0%		
Additional Features												
Compatible battery module	SigenStor BAT 5.0 / 8.0											
Number of modules per controller	1 ~ 6										pcs	
Battery module voltage range	600 ~ 900											
Peak output power (10 seconds)	7500	9000	12000	15000	18000	22500	25500	30000	30000	36000	W	
Nominal output voltage	380 / 400											
Protection												
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ² , AC overcurrent/overvoltage/short-circuit protection, Type II DC/AC surge protection, Anti-islanding protection											
General Data												
Dimensions (W / H / D)	700 / 300 / 283										mm	
Weight	36											kg
Storage temperature range	-40 ~ 70											°C
Operating temperature range	-30 ~ 60											°C
Relative humidity range	0% ~ 95%											
Max. operating altitude	4000											m
Cooling	Smart air cooling											
Ingress protection rating	IP66											
Installation method	Wall-mounted											
Communication	WLAN / Fast Ethernet / RS485 / Sigen CommMod (4G/3G/2G)											
Standard Compliance												
Standard ³	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 61000-6-1, IEC/EN 61000-6-2											

1. Sigen Hybrid Inverter 30.0 kW Three Phase is only available in specific regions. Please contact Sigenenergy or local distributors for details.
2. This is an optional feature only supported in certain models, please contact Sigenenergy for more information.
3. For all standards refer to the certificates category on the Sigenenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.